



- Enhanced enterprise security with optional Intel vPro, Windows disk encryption, TPM 2.0 and many more multi-factor authentication options
- 10th Generation Intel[®] Core[™] i7 / i5 vPro[™] Processor
- 11.6" LumiBond® display with Getac sunlight readable technology and capacitive touchscreen
- LifeSupport[™] battery swappable technology
- Optional dual mode touchscreen (multi-touch and digitizer)





SPECIFICATIONS

| Operating System | Windows 10 Pro Windows 11 Pro | | |
|---------------------------|---|--|--|
| Mobile Computing Platform | Intel [®] Core™ i5-10210U Processor 1.6GHz Max. 4.2GHz with Intel [®] Turbo Boost Technology - 6MB Intel [®] Smart Cache | | |
| | Platform options: | | |
| | Intel [®] Core™ i5-10310U vPro™ Processor 1.7GHz | | |
| | Max. 4.4GHz with Intel [®] Turbo Boost Technology | | |
| | - 6MB Intel [®] Smart Cache | | |
| | Intel [®] Core™ i7-10510U Processor 1.8GHz | | |
| | Max. 4.9GHz with Intel [®] Turbo Boost Technology | | |
| | - 8MB Intel [®] Smart Cache | | |
| | Intel [®] Core™ i7-10610U vPro™ Processor 1.8GHz Max. 4.9GHz with Intel [®] Turbo Boost Technology - 8MB Intel [®] Smart Cache | | |
| | - 8MB Intel [®] Smart Cache | | |
| VGA Controller | Intel [®] UHD Graphics | | |
| Display | 11.6" IPS TFT LCD FHD (1920 x 1080) | | |
| | Protection film | | |
| | 800 nits LumiBond [®] display with Getac sunlight readable | | |
| | technology | | |
| | Capacitive multi-touch screen | | |
| Ctorage 9 Mamony | 8GB DDR4 | | |
| Storage & Memory | Optional: 16GB / 32GB / 64GB DDR4 | | |
| | | | |
| | 256GB PCIe NVMe SSD | | |
| | Optional: 512GB / 1TB SSD PCIe NVMe SSD | | |
| Keyboard | LED backlit membrane keyboard | | |
| Keyboard | Optional: Rubber keyboard | | |
| | Power button | | |
| | 5 tablet programmable buttons | | |
| | | | |
| Pointing Device | Touchscreen | | |
| | - Capacitive multi-touch screen | | |
| | - Optional: Dual mode touchscreen (multi-touch and digitizer) | | |
| | Touchpad | | |
| | - Glide touchpad with left-click and right-click buttons | | |



| Expansion Slots | Smart card reader x 1 ⁱ Optional: 1D/2D imager barcode reader ⁱ | | |
|-------------------------------|--|--|--|
| | | | |
| /O Interface | FHD webcam x 1 " | | |
| | Audio in/out combo x 1 | | |
| | DC in Jack x 1 | | |
| | USB 3.2 Gen 2 Type-C x 1 | | |
| | USB 3.2 Gen 2 Type-A x 2 | | |
| | LAN (RJ45) x 1 | | |
| | HDMI 1.4 x 1 | | |
| | Serial port (9-pin; D-sub) x 1 | | |
| | Docking connector x 1 | | |
| | Optional: SIM card slot x 1 (Mini-SIM, 2FF) | | |
| | Optional: Windows Hello face-authentication camera (front- | | |
| | facing) x 1 " | | |
| | Optional: RF antenna pass-through for GPS, WWAN and | | |
| | WLAN | | |
| | Optional: 8M pixels auto focus rear camera x 1 | | |
| Communication Interface | 10/100/1000 base-T Ethernet | | |
| | Intel [®] Wi-Fi 6 AX200, 802.11ax | | |
| | Bluetooth (v5.2) ⁱⁱⁱ | | |
| | Optional: Dedicated GPS | | |
| | Optional: 4G LTE mobile broadband ^{iv} | | |
| Security Features | TPM 2.0 | | |
| | Kensington lock | | |
| | Optional: Intel [®] vPro™ Technology | | |
| | Optional: HF RFID reader and Smart card reader ^v | | |
| | Optional: Fingerprint reader | | |
| Power | AC adapter (65W, 100-240VAC, 50/60Hz) | | |
| rowei | Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2 | | |
| | LifeSupport [™] battery swappable technology | | |
| | Enesupport – battery swappable technology | | |
| Dimension (W x D x H) & Weigh | 313 x 238 x 39mm (12.32" x 9.37" x 1.53") | | |
| | 2.1kg (4.63lbs) ^{vi} | | |
| Rugged Features | MIL-STD-810H certified | | |
| | IP65 certified | | |
| | MIL-STD-461G certified ^{vii} | | |
| | Vibration & 4ft (1.2m) drop resistant viii | | |
| | Optional: ANSI/UL 121201, CSA C22.2 NO. 213 (Class I, Divisio | | |
| | 2, Groups A, B, C, D) ^{ix} | | |
| | Optional: Salt fog certified | | |

| Environmental Specifications | Temperature [×] : - Operating: -29°C to 63°C / -20°F to 145°F - Storage: -51°C to 71°C / -60°F to 160°F | | |
|------------------------------|--|--|--|
| | | | |
| | Humidity: | | |
| | - 95% RH, non-condensing | | |
| Pre-installed software | Getac Utility | | |
| | Getac Camera | | |
| | Getac Geolocation | | |
| | Getac Barcode Manager ^{xi} | | |
| | Optional: Absolute Persistence® | | |
| Optional software | Getac Driving Safety Utility | | |
| | Getac Device Monitoring System (GDMS) | | |
| | Getac VGPS Utility ^{xii} | | |
| Accessories | Battery (11.1V, typical 2100mAh; min. 2040mAh) | | |
| | AC adapter (65W, 100-240VAC) | | |
| | Capacitive stylus with tether | | |
| | Optional: | | |
| | Carry bag | | |
| | Battery (11.1V, typical 2100mAh; min. 2040mAh) | | |
| | Multi-Bay charger (Dual-Bay) | | |
| | Multi-Bay charger (Eight-Bay) | | |
| | AC adapter (65W, 100-240VAC) | | |
| | Office dock AC adapter (90W, 100-240VAC) | | |
| | MIL-STD-461 AC adapter (90W, 100-240VAC) | | |
| | DC-DC vehicle adapter (120W, 11-32VDC) | | |
| | Digitizer pen | | |
| | Capacitive stylus with tether | | |
| | Protection film | | |
| | Hard handle | | |
| | X strap | | |
| | Shoulder strap (2-point) Vehicle cradle ^{xiii} | | |
| | Venicle cradie Vehicle dock ^{xiii} | | |
| | Office dock | | |
| | Spare SSD kit | | |
| | 100W Type-C adapter | | |
| | Getac rugged keyboard | | |
| | | | |

Getac 4

Bumper-to-Bumper warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.

Standard

3 years Bumper-to-Bumper

- I. Smart card reader, Optional 1D/2D imager barcode reader are mutually exclusive options.
- II. FHD webcam and optional Windows Hello face-authentication camera (front-facing) are mutually exclusive options.
- III. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- IV. Units with 4G LTE option come with an embedded SIM card slot.
- V. 13.56MHz contactless HF RFID/NFC reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
- VI. Weight and dimensions vary from configurations and optional accessories.
- VII. MIL-STD-461 90W AC adapter sold separately.
- VIII. Drop test results vary from configurations and optional accessories.
- IX. Available with limited configurations and environment conditions.
- X. Tested by an independent third-party test lab following MIL-STD-810H.
- XI. Available when barcode reader option is selected.
- XII. Models require either embedded or standalone GPS module.
- XIII. Gamber Johnson and Havis vehicle docks are e-mark certified.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.



| | Vehicle Dock | Office Dock |
|----------------------|---------------------|-------------|
| Serial Port | 2 | 2 |
| External VGA | 1 | 1 |
| Microphone | 1 | 1 |
| Audio Output | 1 | 1 |
| DC in Jack | 1 | 1 |
| USB | 4 | 4 |
| LAN | 1 | 1 |
| HDMI | 1 | 1 |
| RF Antenna Connector | 3 (WWAN, WLAN, GPS) | - |

Getac USA

15495 Sand Canyon Ave. Suite 350 Irvine, CA 92618 Tel : 949-681-2900 GetacSales_US@getac.com I www.getac.com/us/ Copyright © 2022 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved. Information provided herewith is for reference only, available specification shall be subjected to quotation by request.

